



## SELE-LOCKING NYLON CABLE TIES




Product Name: SELE-LOCKING NYLON CABLE TIES

### Description:

Material: Nylon 66,94v-2 certificated by UL,heat-resisting,erosion control,insulate well and not apt to age.

Operating temperature: -40C to 85C

Color: Natural(or white,standard color),UV black and other colors are available as requestd.



| Item No. | L       |     | W    | MAX BUNDLE DIA(MM) | TENSILE STRENGTH |     | Packing        |
|----------|---------|-----|------|--------------------|------------------|-----|----------------|
|          | INCH    | MM  | (MM) |                    | LBS              | KGS |                |
| HS-60A   | 2 3/8"  | 60  | 2.5  | 11                 | 18               | 8   | 100PCS&1000PCS |
| HS-80A   | 3 3/16" | 80  | 2.5  | 16                 | 18               | 8   |                |
| HS-100A  | 4"      | 100 | 2.5  | 22                 | 18               | 8   |                |
| HS-120A  | 4 3/4"  | 120 | 2.5  | 30                 | 18               | 8   |                |
| HS-150A  | 6"      | 150 | 2.5  | 35                 | 18               | 8   |                |
| HS-160A  | 6 1/4"  | 160 | 2.5  | 40                 | 18               | 8   |                |
| HS-200A  | 8"      | 200 | 2.5  | 50                 | 18               | 8   |                |
| HS-120B  | 4 3/4"  | 120 | 3.5  | 30                 | 40               | 18  | 100PCS&500PCS  |
| HS-150B  | 6"      | 150 | 3.5  | 35                 | 40               | 18  |                |
| HS-180B  | 7"      | 180 | 3.5  | 42                 | 40               | 18  |                |
| HS-200B  | 8"      | 200 | 3.5  | 50                 | 40               | 18  |                |
| HS-250B  | 10"     | 250 | 3.5  | 65                 | 40               | 18  |                |
| HS-280B  | 11"     | 280 | 3.5  | 70                 | 40               | 18  |                |
| HS-300B  | 11 5/8" | 300 | 3.5  | 80                 | 40               | 18  |                |
| HS-370B  | 14 1/2" | 370 | 3.5  | 102                | 40               | 18  |                |
| HS-120C  | 4 3/4"  | 120 | 4.5  | 24                 | 50               | 22  |                |
| HS-150C  | 6"      | 150 | 4.5  | 35                 | 50               | 22  |                |
| HS-190C  | 7 1/2"  | 190 | 4.5  | 46                 | 50               | 22  |                |
| HS-200C  | 8"      | 200 | 4.5  | 50                 | 50               | 22  |                |
| HS-250C  | 10"     | 250 | 4.5  | 65                 | 50               | 22  |                |
| HS-280C  | 11"     | 280 | 4.5  | 70                 | 50               | 22  |                |

|          |            |     |     |     |     |    |        |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
|----------|------------|-----|-----|-----|-----|----|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| HS-300C  | 11 5/8"    | 300 | 4.8 | 82  | 50  | 22 |        |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
| HS-350C  | 13 3/4"    | 350 | 4.8 | 90  | 50  | 22 |        |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
| HS-370C  | 14 1/2"    | 370 | 4.8 | 102 | 50  | 22 |        |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
| HS-400C  | 15 3/4"    | 400 | 4.8 | 105 | 50  | 22 |        |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
| HS-450C  | 17 3/4"    | 450 | 4.8 | 130 | 50  | 22 |        |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
| HS-500C  | 19 11/16"  | 500 | 4.8 | 140 | 50  | 22 |        |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
| HS-530C  | 20 4/5''   | 530 | 4.8 | 147 | 50  | 22 |        |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
| HS-250DS | 10''       | 250 | 6.8 | 65  | 90  | 40 |        |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
| HS-300DS | 11 5/8''   | 300 | 6.8 | 80  | 90  | 40 |        |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
| HS-370DS | 14 1/2''   | 370 | 6.8 | 102 | 90  | 40 |        |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
| HS-150D  | 6"         | 150 | 7.6 | 33  | 120 | 55 |        |        |        |        |        |        |        |        |        |        | 100PCS |        |        |        |        |
| HS-200D  | 8"         | 200 | 7.6 | 50  | 120 | 55 | 100PCS |        |        |        |        |        |        |        |        |        |        |        |        |        |        |
| HS-250D  | 10"        | 250 | 7.6 | 63  | 120 | 55 |        | 100PCS |        |        |        |        |        |        |        |        |        |        |        |        |        |
| HS-300D  | 11 5/8"    | 300 | 7.6 | 82  | 120 | 55 |        |        | 100PCS |        |        |        |        |        |        |        |        |        |        |        |        |
| HS-350D  | 13 3/4"    | 350 | 7.6 | 90  | 120 | 55 |        |        |        | 100PCS |        |        |        |        |        |        |        |        |        |        |        |
| HS-370D  | 14 1/2"    | 370 | 7.6 | 102 | 120 | 55 |        |        |        |        | 100PCS |        |        |        |        |        |        |        |        |        |        |
| HS-400D  | 15 3/4"    | 400 | 7.6 | 105 | 120 | 55 |        |        |        |        |        | 100PCS |        |        |        |        |        |        |        |        |        |
| HS-450D  | 17 3/4"    | 450 | 7.6 | 118 | 120 | 55 |        |        |        |        |        |        | 100PCS |        |        |        |        |        |        |        |        |
| HS-500D  | 19 11/16"  | 500 | 7.6 | 150 | 120 | 55 |        |        |        |        |        |        |        | 100PCS |        |        |        |        |        |        |        |
| HS-550D  | 21 11/16'' | 550 | 7.6 | 160 | 120 | 55 |        |        |        |        |        |        |        |        | 100PCS |        |        |        |        |        |        |
| HS-430DL | 17 "       | 430 | 9   | 112 | 175 | 80 |        |        |        |        |        |        |        |        |        | 100PCS |        |        |        |        |        |
| HS-550DL | 21 11/16"  | 550 | 9   | 160 | 175 | 80 |        |        |        |        |        |        |        |        |        |        |        | 100PCS |        |        |        |
| HS-650DL | 25 9/16"   | 650 | 9   | 190 | 175 | 80 |        |        |        |        |        |        |        |        |        |        |        |        | 100PCS |        |        |
| HS-760DL | 30"        | 760 | 9   | 225 | 175 | 80 |        |        |        |        |        |        |        |        |        |        |        |        |        | 100PCS |        |
| HS-810DL | 32''       | 810 | 9   | 239 | 175 | 80 |        |        |        |        |        |        |        |        |        |        |        |        |        |        | 100PCS |

|           |           |      |      |     |     |     |  |
|-----------|-----------|------|------|-----|-----|-----|--|
| HS-920DL  | 36 1/4"   | 920  | 9    | 265 | 175 | 80  |  |
| HS-1168DL | 46"       | 1168 | 9    | 360 | 175 | 80  |  |
| HS-550FL  | 21 11/16" | 550  | 12.7 | 160 | 250 | 114 |  |

  
**SYNERGY TELECOM (P) LTD.**  
 D-15, RPS Flats, E-Block, Vasant Pur, New Delhi - 110 011 (INDIA)  
 Phone: +91-11-26533349 Fax: +91-11-26538830 Mobile: +91-9810338994  
 Email: [proddeep@connectorhq.com](mailto:proddeep@connectorhq.com), MSN: [proddeep@proddeep@synergy99@hotmail.com](mailto:proddeep@proddeep@synergy99@hotmail.com)  
 PRINCIPAL SITE: <http://www.vitrc.com/info> Skype Account: proddeepag  
 My trademarker ID: synergytelecom - www.zl.com/sdcom.info