



MALE PRE-INSULATING JOINT

Subordinate categories: head and connector terminal


Lead section :0.5-1 .5 mm² (AWG 22-16) Max Current: 1max = 10A

Model Item No	Nema TAD (mm)	Size Dimension (mm)						Color,
		B	d	D	L	H		
MDD1.25-110 (5)	0.5x2.8	2.8	1.7	4.3	17.7	5.0	Red Red	
MDD1.25-110 (8)	0.8x2.8	2.8	1.7	4.3	17.7	5.0		
MDD1.25-110 (5)	0.5x4.75	4.75	1.7	4.3	20.0	5.0		
MDD1.25-110 (8)	0.8x4.75	4.75	1.7	4.3	20.0	5.0		
MDD1.25-250	0.8x6.35	6.35	1.7	4.3	21.0	5.0		



Lead section :1.5-2 .5 mm² (AWG 16-14) Max Current: 1max = 15A

Model Item No	Nema TAD (mm)	Size Dimension (mm)						Color,
		B	d	D	L	H		
MDD2-187 (5)	0.5x4.75	4.75	2.3	4.3	20.0	5.0	Blue Blue	
MDD2-187 (8)	0.8x4.75	4.75	2.3	4.3	20.0	5.0		
MDD2-250	0.8x6.35	6.35	2.3	4.3	20.0	5.0		



Conductor cross-section :4-6mm² (AWG 12-10) Max Current: 1max = 24A

Model Item No	Nema TAD (mm)	Size Dimension (mm)						Color,
		B	d	D	L	H		
MDD5.5-250	0.8x6.35	6.35	3.4	5.7	25.0	13.0	Yellow Yellow	

