

SYNERGY TELECOM P. LTD

BNC M RG 11 CRIMP



Electrical Specification

| | |
|---------------------------------|--|
| Characteristic Impedance | 50 ohm |
| Frequency Range | DC- 4 GHz |
| VSWR | <1.2 |
| Contact Resistance | Inner Conductor : < 1.5 m Ω Outer Conductor : < 1.0 m Ω |
| Dielectric withstanding Voltage | >2500V RMS, 50Hz, At sea Level |
| Dielectric Resistance | > 5000 M Ω |
| RoHS | Compliance |

Mechanical

| | |
|-------------------|------------------|
| Durability Mating | cycle \geq 500 |
|-------------------|------------------|

Material Specification

| | Material | Plating |
|------------------|-----------------|--------------|
| Body | Brass | White Bronze |
| Insulator | Teflon/PTFE | |
| Center Conductor | Phosphor Copper | Gold(AU) |
| Ferrule | Annealed copper | Ni |

Environmental

| | |
|-------------------|-----------------|
| Temperature Range | - 10°C – +55 °C |
|-------------------|-----------------|

WZ-47 BUDHELLA VILLAGE, VIKASPURI, NEW DELHI – 110018

PHONE: 011-28533349, MOB: 9810138894/9212558066, FAX: 011-28533349

EMAIL: info@rfconnector.in, WEBSITE: <http://rfconnector.in/>