



N Male for 1/2" Cable :-

Description	RF Connector
Note	N Male for 1/2 cable



Impedance		50Ω
Contact resistance (MΩ)	Inner conductor	≤1mΩ
	Outer conductor	≤0.25 mΩ
Insulation resistance (MΩ)		≥5000MΩ
Withstanding voltage AC□V/min□		≥2500V
V SWR		(0~2.2GHz) ≤1.10
		(2.2~3GHz) ≤1.15
Insertion loss (dB)		≤0.1 at 3GHz
PIM3 @2x20W		≤-145dBc
Water-proof		IP67
Durability		500 Times

pdfMachine - is a pdf writer that produces quality PDF files with ease!

Get yours now!

"Thank you very much! I can use Acrobat Distiller or the Acrobat PDFWriter but I consider your product a lot easier to use and much preferable to Adobe's" A.Sarras - USA



N Female for 1/2" Cable :-

Description	RF Connector
Note	N Female for 1/2 cable



Impedance		50Ω
Contact resistance (MΩ)	Inner conductor	≤1mΩ
	Outer conductor	≤0.25 mΩ
Insulation resistance (MΩ)		≥5000MΩ
Withstanding voltage AC□V/min□		≥2500V
VSWR		(0~2.2GHz) ≤1.10
		(2.2~3GHz) ≤1.15
Insertion loss (dB)		≤0.1 at 3GHz
PIM3 @2x20W		≤-145dBc
Water-proof		IP67
Durability		500times

pdfMachine - is a pdf writer that produces quality PDF files with ease!

Get yours now!

"Thank you very much! I can use Acrobat Distiller or the Acrobat PDFWriter but I consider your product a lot easier to use and much preferable to Adobe's" A.Sarras - USA



N Male Right angle for 1/2" Cable :-

Description	RF Connector
Note	N Male Right angle for 1/2 cable



Impedance	50Ω	
Contact resistance (MΩ)	Inner conductor	≤1mΩ
	Outer conductor	≤0.25 mΩ
Insulation resistance (MΩ)	≥5000MΩ	
Withstanding voltage AC □V/min □	≥2500V	
V SWR	(0~2.2GHz) ≤1.15	
Insertion loss (dB)	≤0.1 at 3GHz	
PIM3 @2x20W	≤-145dBc	
Water-proof	IP67	
Durability	500 Times	

pdfMachine - is a pdf writer that produces quality PDF files with ease!

Get yours now!

"Thank you very much! I can use Acrobat Distiller or the Acrobat PDFWriter but I consider your product a lot easier to use and much preferable to Adobe's" A.Sarras - USA



N Female for 7/8" Cable :-

Description	RF Connector
Note	N Female for 7/8 cable



Impedance		50Ω
Contact resistance (MΩ)	Inner conductor	≤1mΩ
	outer conductor	≤0.25 mΩ
Insulation resistance (MΩ)		≥5000MΩ
Withstanding voltage AC□V/min□		≥2500V
VSWR		(0~2.2GHz) ≤1.10
		(2.2~3GHz) ≤1.15
Insertion loss (dB)		≤0.1 at 3GHz
PIM3 @2x20W		≤-145dBc
Water-proof		IP67
Durability		500times

pdfMachine - is a pdf writer that produces quality PDF files with ease!

Get yours now!

"Thank you very much! I can use Acrobat Distiller or the Acrobat PDFWriter but I consider your product a lot easier to use and much preferable to Adobe's" A.Sarras - USA



N Male for 7/8" Cable :-

Description	RF Connector
Note	N Male for 7/8 cable



	Impedance	50Ω
Contact resistance (MΩ)	Inner conductor	≤1mΩ
	outer conductor	≤0.25 mΩ
Insulation resistance (MΩ)		≥5000MΩ
Withstanding voltage AC□V/min□		≥2500V
VSWR		(0~2.2GHz) ≤1.10
		(2.2~3GHz) ≤1.15
Insertion loss (dB)		≤0.1 at 3GHz
PIM3 @2x20W		≤-145dBc
Water-proof		IP67
Durability		500□

pdfMachine - is a pdf writer that produces quality PDF files with ease!

Get yours now!

"Thank you very much! I can use Acrobat Distiller or the Acrobat PDFWriter but I consider your product a lot easier to use and much preferable to Adobe's" A.Sarras - USA



N Male for 13/8" Cable :-

Description	RF Connector
Note	N Male for 13/8 cable



Impedance		50Ω
Contact resistance (MΩ)	Inner conductor	≤1mΩ
	Outer conductor	≤0.25 mΩ
Insulation resistance (MΩ)		≥5000MΩ
Withstanding voltage AC□V/min□		≥2500V
V SWR		(0~2.2GHz) ≤1.10
		(2.2~3GHz) ≤1.15
Insertion loss (dB)		≤0.1 at 3GHz
PIM3 @2x20W		≤-145dBc
Water-proof		IP67
Durability		500 Times

pdfMachine - is a pdf writer that produces quality PDF files with ease!

Get yours now!

"Thank you very much! I can use Acrobat Distiller or the Acrobat PDFWriter but I consider your product a lot easier to use and much preferable to Adobe's" A.Sarras - USA



N Female for 13/8" Cable :-

Description	RF Connector
Note	N Female for 13/8 cable



	Impedance	50Ω
Contact resistance (MΩ)	Inner conductor	≤1mΩ
	Outer conductor	≤0.25 mΩ
Insulation resistance (MΩ)		≥5000MΩ
Withstanding voltage AC□V/min□		≥2500V
V SWR		(0~2.2GHz) ≤1.10
		(2.2~3GHz) ≤1.15
Insertion loss (dB)		≤0.1 at 3GHz
PIM3 @2x20W		≤-145dBc
Water-proof		IP67
Durability		500 Times

pdfMachine - is a pdf writer that produces quality PDF files with ease!

Get yours now!

"Thank you very much! I can use Acrobat Distiller or the Acrobat PDFWriter but I consider your product a lot easier to use and much preferable to Adobe's" A.Sarras - USA



N Male for 1/2"SF Cable :-

Description	RF Connector
Note	N Male for 1/2 sf cable



Impedance		50Ω
Contact resistance (MΩ)	Inner conductor	≤1mΩ
	Outer conductor	≤0.25 mΩ
Insulation resistance (MΩ)		≥5000MΩ
Withstanding voltage AC□V/min□		≥2500V
V SWR		(0~2.2GHz) ≤1.10
		(2.2~3GHz) ≤1.15
Insertion loss (dB)		≤0.1 at 3GHz
PIM3 @2x20W		≤-145dBc
Water-proof		IP67
Durability		500 Times

pdfMachine - is a pdf writer that produces quality PDF files with ease!

Get yours now!

"Thank you very much! I can use Acrobat Distiller or the Acrobat PDFWriter but I consider your product a lot easier to use and much preferable to Adobe's" A.Sarras - USA



N Female for 1/2"SF Cable :-

Description	RF Connector
Note	N Female for 1/2 sf cable



	Impedance	50Ω
Contact resistance (MΩ)	Inner conductor	≤1mΩ
	Outer conductor	≤0.25 mΩ
Insulation resistance (MΩ)		≥5000MΩ
Withstanding voltage AC□V/min□		≥2500V
V SWR		(0~2.2GHz) ≤1.10
		(2.2~3GHz) ≤1.15
Insertion loss (dB)		≤0.1 at 3GHz
PIM3 @2x20W		≤-145dBc
Water-proof		IP67
Durability		500 Times

pdfMachine - is a pdf writer that produces quality PDF files with ease!

Get yours now!

"Thank you very much! I can use Acrobat Distiller or the Acrobat PDFWriter but I consider your product a lot easier to use and much preferable to Adobe's" A.Sarras - USA



N Male for 1/4”SF Cable :-

Description	RF Connector
Note	N Male for 1/4 sf cable



Specification	Impedance	50Ω
Contact resistance (MΩ)	Inner conductor	≤1mΩ
	Outer conductor	≤0.25 mΩ
Insulation resistance (MΩ)		≥5000MΩ
Withstanding voltage AC□V/min□		≥1500V
V SWR		(0~2.2GHz) ≤1.10
		(2.2~3GHz) ≤1.15
Insertion loss (dB)		≤0.1 at 3GHz
PIM3 @2x20W		≤-145dBc
Water-proof		IP67
Durability		500 Times

pdfMachine - is a pdf writer that produces quality PDF files with ease!

Get yours now!

“Thank you very much! I can use Acrobat Distiller or the Acrobat PDFWriter but I consider your product a lot easier to use and much preferable to Adobe's” A.Sarras - USA



N Female for 1/4" Cable :-

Description	RF Connector
Note	N Female for 1/4 cable



Impedance		50Ω
Contact resistance (MΩ)	Inner conductor	≤1mΩ
	Outer conductor	≤0.25 mΩ
Insulation resistance (MΩ)		≥5000MΩ
Withstanding voltage AC□V/min□		≥1500V
V SWR		(0~2.2GHz) ≤1.10
		(2.2~3GHz) ≤1.15
Insertion loss (dB)		≤0.1 at 3GHz
PIM3 @2x20W		≤-145dBc
Water-proof		IP67
Durability		500 Times

pdfMachine - is a pdf writer that produces quality PDF files with ease!

Get yours now!

"Thank you very much! I can use Acrobat Distiller or the Acrobat PDFWriter but I consider your product a lot easier to use and much preferable to Adobe's" A.Sarras - USA



N Male for 1/4" Cable :-

Description	RF Connector
Note	N Male for 1/4 cable



Impedance		50Ω
Contact resistance (MΩ)	Inner conductor	≤1mΩ
	Outer conductor	≤0.25 mΩ
Insulation resistance (MΩ)		≥5000MΩ
Withstanding voltage AC□V/min□		≥1500V
V SWR		(0~2.2GHz) ≤1.10
		(2.2~3GHz) ≤1.15
Insertion loss (dB)		≤0.1 at 3GHz
PIM3 @2x20W		≤-145dBc
Water-proof		IP67
Durability		500 Times

pdfMachine - is a pdf writer that produces quality PDF files with ease!

Get yours now!

"Thank you very much! I can use Acrobat Distiller or the Acrobat PDFWriter but I consider your product a lot easier to use and much preferable to Adobe's" A.Sarras - USA



N Female Flange Connector :-

Note	N Female Flange Connector
-------------	---------------------------



Impedance		50Ω
Contact resistance (MΩ)	Inner conductor	≤1mΩ
	Outer conductor	≤0.25 mΩ
Insulation resistance (MΩ)		≥5000MΩ
Withstanding voltage AC□V/min□		≥2500V
VSWR		(0~3GHz) ≤1.10
Insertion loss (dB)		≤0.1 at 3GHz
PIM3 @2x20W		≤-153dBc
Water-proof		IP67
Durability		500times

SYNERGY TELECOM (P) LTD.
 B-15, RPS Flats, E-Block, Vileca Park, New Delhi - 110 016 (INDIA)
 Phone: +91-11-26533349 Fax: +91-11-26534435 Mobile: +91-981038894
 Email: proddeep@rfconnectorhouse.com, MSK_proddeep@rediffmail.com
 PRINCIPAL SITE: <http://www.vilascem.info> Skype Account: proddeep
 My trademanager ID: synergytelecom www.rfconnector.com

pdfMachine - is a pdf writer that produces quality PDF files with ease!
Get yours now!
 "Thank you very much! I can use Acrobat Distiller or the Acrobat PDFWriter but I consider your product a lot easier to use and much preferable to Adobe's" A.Sarras - USA