






UY Connectors :-

Which One you Require with there Part No. along with Quantity :-

Butt splicing				
Part no.	UY C	UY2 C	UR C	UR2 C
Type of joint	2 wire -straight		3 wire – straight or bridge	
Conductor ϕ	0.32-0.65 mm	0.32-0.90 mm	0.32-0.65 mm	0.32-0.90 mm
Insulation ϕ	Max 1.55 mm	Max 1.65 mm	Max 1.65 mm	Max 2.08mm
Protection	Sealant filled			

Butt splicing				
Part no.	UY2 P	UY2 PD	UR2 P	UR2 PD
Type of joint	2 wire -straight		3 wire – straight or bridge	
Conductor ϕ	0.32 to 0.90 mm.			
Insulation ϕ	Max 2.08 mm			
Protection	Sealant filled	Dry	Sealant filled	Dry


SYNERGY TELECOM (P) LTD.
 13-15, RPS Flats, E-Block, Vasant Vihar, New Delhi - 110 018 (INDIA)
 Phone: +91-11-28533349 Fax: +91-11-28531435 Mobile: +91-981038894
 Email: pradeep@rfconnectorhouse.com, MSN: pradeepgrowsal@synergy@hotmail.com
 PRINCIPAL SITE: <http://www.vincom.info> Skype Account: pradeepgog
 My trademanager ID: synergytelecom www.rfconnectors.info

pdfMachine
A pdf writer that produces quality PDF files with ease!
 Produce quality PDF files in seconds and preserve the integrity of your original documents. Compatible across nearly all Windows platforms, simply open the document you want to convert, click "print", select the "Broadgun pdfMachine printer" and that's it! Get yours now!