



Single BNC m To RJ45 Type Balun



Specifications

Normal Output Level 1Vp-p/ 75 Ω ,
 Bandwidth Video: DC to 6 MHz.
 Differential Gain \pm 4%
 Differential Phase \pm 2 $^{\circ}$
 Signal-noise-ratio 60dB
 Anti-interference Built-in
 Insertion Loss Less than 1.5 dB per pair over the frequency range from DC to 6 MHz
 Max. Distance Color Cat 3-492 ft (150m); Cat 5-750 ft (225m)
 Max. Distance B&W Cat 3-1246 ft (380m); Cat 5-1804 ft (550m)
 Temperature Operating: -25 $^{\circ}$ to 70 $^{\circ}$ C; Storage: -25 $^{\circ}$ to 85 $^{\circ}$ C
 Humidity Up to 95%
 Enclosure ABS fire retardant plastic
 Weight 23g
 Dimensions Length 70mm \times Width 30mm \times Height 22mm

Synergy Telecom P Ltd.
 13-15 RPS flats, E-block, Vikaspuri N Delhi, 110018... India
 Phone-91 11 28533349, Mobile 91-98101 38894, Fax -91 11 2853 1435,
 pradeep@rfconnectorhouse.com ; MSN - pradeepagrawalsynergy@hotmail.com
 Skype Account - pradeepag, My trademanager ID -synergytelecom ;
<http://www.rfconnector.info/>

