



2 Watt N Male Termination :-

Characters:

1. Wide operating frequency range
2. LOW VSWR
3. Anti-pulse, high burning resistance




Application: Mainly used in communication, radar and indoor distribution system.

Specification:

P/N	SX-TJ2W
Freq. range	DC-4GHz
Power	2W
VSWR	≤1.1
Impedance	50Ω
Connector	N (SMA) -Male
Operating Temp.	-40~+70℃
Storage Temp.	-60~+100℃
Weight	35g

Drawing and Dimension:





SYNERGY TELECOM (P) LTD.

13-15, RPS Flats, E-Block, Vasant Puri, New Delhi - 110 018 (INDIA)
 Phone: +91-11-28533349 Fax: +91-11-28531435 Mobile: +91-9810138894
 Email: pradeep@rfconnectorhouse.com, MSN: pradeepagrowal@synergy@hotmail.com
 PRINCIPAL SITE: <http://www.vinncom.info> Skype Account: pradeepag
 My trademanager ID: synergytelecom www.rfconnectors.info

pdfMachine

Is a pdf writer that produces quality PDF files with ease!

Produce quality PDF files in seconds and preserve the integrity of your original documents. Compatible across nearly all Windows platforms, if you can print from a windows application you can use pdfMachine.

Get yours now!