



Dummy Load - 250 Watt :-

Electrical Specification

Operating Frequency:	DC~3000MHZ
Tolerance:	-----
Attenuation:	-----
V.S.W.R	1:1.2/MAX
Isolation Rate	-----
Amplitude Unbalance	-----
Phase Unbalance	-----
Input Power	250 0Watt
Impedence	50Ω/Nominal

Physical Specification

Operating Temperature:	-40℃ ~ +80℃
Dimension (W*D*H/mm)	230*160*87
Weight (gram)	4200g
Connector-input	N/SMA
Connector-output	-----



[Product image]

Plating

Inner conductor	Silver Plated
Outer Conductor	Nickel Plated
Other Metal Parts	Black Plated

Material Specification

Inner Conductor	Beryllium Copper or Spring Bronze
Other Metal Parts (Housing)	Aluminum



SYNERGY TELECOM (P) LTD.

13-15, RP5 Flats, E-Block, Vasant Puri, New Delhi - 110 018 (INDIA)

Phone: +91-11-28533349 Fax: +91-11-28531435 Mobile: +91-9810138894

Email: pradeep@rfconnectorhouse.com, MSN: pradeepagrowal@synergy@hotmail.com

PRINCIPAL SITE: <http://www.vinncom.info> Skype Account: pradeepag

My trademanager ID: synergytelecom www.rfconnectors.info

pdfMachine

A pdf writer that produces quality PDF files with ease!

Produce quality PDF files in seconds and preserve the integrity of your original documents. Compatible across nearly all Windows platforms, simply open the document you want to convert, click "print", select the "Broadgun pdfMachine printer" and that's it! Get yours now!